

#### Issue date 11-Jun-2014

# Safety Data Sheet

Version 1

# 1. Identification of the Substance/Preparation and of the Company/Undertaking

<u>Product Identifier</u> Product name Chemical name	TOTAL CARE REACT PLUS BASEBOARD & FLOOR STRIPPER 7-7903-3		
<u>Other means of identification</u> Product code Synonyms	FG 437-3462-0360 Baseboard and wax stripper.		
Recommended use of the chemical	and restrictions on use		
Recommended Use	Strips old wax, acrylics and other coatings from floors and baseboards.		
Uses advised against	Do not use on asphalt tile. Test on small area before using on plexiglass and plastic		
	surfaces.		
Details of the supplier of the safety	data sheet		
Supplier Address	Manufacturer Address		
Area Distributors, Inc.	Chase Products Co.		
218 Vermont	2727 Gardner Road		
Quincy, IL 62306	Broadview, IL 60155		
800-828-2826	708-273-1121		
Emergency Telephone Number			

# Company Phone Number708-865-100024 Hour Emergency Phone Number1-800-255-3924

#### 2. Hazards Identification

#### **Classification**


Acute toxicity - Inhalation (Gases)	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Germ Cell Mutagenicity	Category 1B
carcinogenicity	Category 1A

#### Label Elements

#### EMERGENCY OVERVIEW

### DANGER

hazard statements HARMFUL IF INHALED CAUSES SKIN IRRITATION Causes serious eye irritation May cause genetic defects May cause cancer



#### **Precautionary Statements - Prevention**

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Use personal protective equipment as required Avoid breathing fumes, mist, vapors or spray. Use only outdoors or in a well-ventilated area Wash face, hands and any exposed skin thoroughly after handling

#### **Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing IF ON SKIN: Wash with plenty of soap and water If skin irritation occurs: Get medical advice/attention Take off contaminated clothing and wash before reuse IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

#### **Precautionary Statements - Storage**

Prevent this container from coming in contact with water for a prolonged period of time. Always keep container in a cool, dry place . Store locked up

Do not store at temperatures above 122 F (50 C).

#### **Precautionary Statements - Disposal**

Recycle empty can where available or discard in the trash. Pressurized container: Do not pierce or burn, even after use

# Hazards not otherwise classified (HNOC)

OTHER INFORMATION
• MAY BE HARMFUL IF SWALLOWED
2.17% of the mixture consists of ingredient(s) of unknown toxicity

## 3. Composition/information on Ingredients

Common NameBaseboard and wax stripper.SynonymsBaseboard and wax stripper.Chemical FamilyMIXTURES.Formula7-7903-3Chemical natureAqueous solution of organic solvent.

Chemical name	CAS No	weight-%	Trade secret
2-Butoxyethanol	111-76-2	5-10	*
N-Butane	106-97-8	1-5	*
Morpholine	110-91-8	1-5	*
Propane	74-98-6	1-5	*

Chemical Additions

Hazardous components according to OSHA, are listed when present at 1% or greater. Carcinoges are listed when present at 0.1% or greater.

\* The exact percentage (concentration) of composition has been withheld as a trade secret.

	4. First aid measures
FIRST AID MEASURES	
Eye Contact	Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice.
Skin contact	Wash skin with soap and water. In the case of skin irritation or allergic reactions see a physician.
inhalation	If overcome by vapor, move person to fresh air. Restore respiration if necessary. Get medical attention if injury develops.
INGESTION	Ingestion from an aerosol product is unlikely to occur.
Most important symptoms and eff	fects, both acute and delayed
Symptoms	Acute: Prolonged inhalation of concentrated vapor or mist can cause nasal and respiratory irritation, headaches, dizziness and nausea. Prolonged contact with skin can cause irritation, burning, redness and pain. Contact with eyes causes irritation, burning, tearing, redness and blurred vision. Chronic: 2-butoxyethanol may cause hemolysis of the blood cells leading to possible liver and kidney damage.
Indication of any immediate medic	cal attention and special treatment needed
Note to physicians	None needed.
	5. Fire-fighting measures
Specific hazards arising from the	l <b>ia</b> Caution: Use of water spray when fighting fire may be inefficient. <u>chemical</u> er spray may be used to cool cans in the vicinity of fire or excessive heat to prevent the
Hazardous combustion produ	ctsThermal decomposition may yield gases like ammonia, carbon monoxide, carbon dioxide, formaldehyde and nitrogen compounds.
Sensitivity to Static Discharge	<ul> <li>act Contents under pressure, keep away from heat and open flame.</li> <li>Keep away from heat, sparks, flame, and other sources of ignition (i.e., pilot lights, electric motors and static electricity).</li> </ul>
Protective equipment and precaut As in any fire, wear self-contained bi	<ul> <li>Keep away from heat, sparks, flame, and other sources of ignition (i.e., pilot lights, electric motors and static electricity).</li> </ul>
Protective equipment and precaut As in any fire, wear self-contained bi	<ul> <li>Keep away from heat, sparks, flame, and other sources of ignition (i.e., pilot lights, electric motors and static electricity).</li> <li>tions for firefighters</li> </ul>
Protective equipment and precaut As in any fire, wear self-contained by protective gear.	<ul> <li>Keep away from heat, sparks, flame, and other sources of ignition (i.e., pilot lights, electric motors and static electricity).</li> <li>tions for firefighters</li> <li>reathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full</li> </ul>
Protective equipment and precaut As in any fire, wear self-contained by protective gear.	<ul> <li>Keep away from heat, sparks, flame, and other sources of ignition (i.e., pilot lights, electric motors and static electricity).</li> <li>tions for firefighters reathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full</li> <li>6. Accidental release measures</li> </ul>
Protective equipment and precaut As in any fire, wear self-contained by protective gear. Personal precautions, protective e	<ul> <li>Keep away from heat, sparks, flame, and other sources of ignition (i.e., pilot lights, electric motors and static electricity).</li> <li>tions for firefighters reathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full</li> <li>6. Accidental release measures</li> <li>equipment and emergency procedures</li> </ul>

See Section 12 for additional Ecological Information.

**Environmental Precautions** 

Methods and material for containment and cleaning up			
Methods for Containment	Provide adequate ventilation to area being treated. Soak up spills with chemically inert, absorbent material.		
Methods for cleaning up	Clean contaminated surface thoroughly.		
	7. Handling and Storage		
Precautions for safe handling			
Advice on safe handling	Do not deliberately inhale vapor or spray mist. Avoid getting spray into eyes.		
Conditions for safe storage, including any incompatibilities			
Storage Conditions	Store in a cool, dry place away from heat and open flame. Keep out of reach of children. AEROSOL STORAGE LEVEL I (NFPA-30B) .		
Incompatible Materials	Avoid heat and open flame. Avoid contact with alcohols, ketones, nitrites and strong oxidizing agents.		

# 8. Exposure Controls/Personal Protection

#### Control parameters

#### **Exposure guidelines**

See occupational exposure limits listed below.

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
2-Butoxyethanol 111-76-2	TWA: 20 ppm	TWA: 50 ppm TWA: 240 mg/m <sup>3</sup> (vacated) TWA: 25 ppm (vacated) TWA: 120 mg/m <sup>3</sup> (vacated) S* S*	IDLH: 700 ppm TWA: 5 ppm TWA: 24 mg/m <sup>3</sup>
N-Butane 106-97-8	STEL: 1000 ppm	(vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m <sup>3</sup>	TWA: 800 ppm TWA: 1900 mg/m <sup>3</sup>
Morpholine 110-91-8	TWA: 20 ppm S*	TWA: 20 ppm TWA: 70 mg/m <sup>3</sup> (vacated) TWA: 20 ppm (vacated) TWA: 70 mg/m <sup>3</sup> (vacated) STEL: 30 ppm (vacated) STEL: 105 mg/m <sup>3</sup> (vacated) S* S*	IDLH: 1400 ppm TWA: 20 ppm TWA: 70 mg/m <sup>3</sup> STEL: 30 ppm STEL: 105 mg/m <sup>3</sup>
Propane 74-98-6	TWA: 1000 ppm	TWA: 1000 ppm TWA: 1800 mg/m <sup>3</sup> (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m <sup>3</sup>	IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m <sup>3</sup>

#### Appropriate engineering controls

**Engineering controls** Use with adequate general or local exhaust ventilation.

#### Individual protection measures, such as personal protective equipment

Eye/face Protection	Conventional eyeglasses to guard against splashing.	
Skin and Body Protection	Rubber, vinyl or household type gloves required.	
Respiratory protection	Use in a well-ventilated area ONLY. WHEN USING INDOORS, KEEP WINDOWS AND DOORS OPEN UNTIL FUMES DISSIPATE. A NIOSH-approved air purifying respirator may be necessary where airborne concentrations exceed the exposure levels.	

General hygiene considerations

Wash hands thoroughly after handling.

# 9. Physical and Chemical Properties

#### Information on basic physical and chemical properties

mormation on basic physical and chemical properties				
Physical State appearance color	Aerosol Cloudy, white liquid. white	Odor	Minty	
<u>Property</u> pH Melting point/freezing point Boiling point/boiling range Flash Point	<u>Values</u> 9.75 to 10.19 Not applicable Water 212 °F/100 °C Not Available. This is an aerosol product for which Flame Projection is inches. Temperatures above 120 F may cause cans to burst.	Remarks • Method		
Evaporation Rate flammability (solid, gas) Flammability Limits in Air Upper flammability limits Lower Flammability Limit vapor pressure	Faster than butyl acetate Not available Not available			
Specific gravity Water solubility	1.0 concentrate	Soluble in water		
OTHER INFORMATION				
VOC content (%) density Bulk Density	17.35 8.33 lb/gal			
	10. Stability and React	tivity		
<u>Reactivity</u> Not applicable	Not applicable			
<u>Chemical stability</u> Stable.				
Possibility of hazardous reactions Temperatures above 120 F may cause	se cans to burst with force.			
hazardous polymerization	Hazardous polymerization does not or	ccur.		
Conditions to Avoid Temperatures above 120 F.				
Incompatible Materials Avoid heat and open flame. Avoid co	ntact with alcohols, ketones, nitrites and	strong oxidizing agents.		
Hazardous decomposition product Thermal decomposition may yield ga	t <u>s</u> ses like carbon monoxide and carbon di	oxide.		
	11. Toxicological Inform	nation		
Information on likely routes of exp	osure			
Product Information	Primary routes of entry: Eye contact, s consider unlikely).	skin contact, inhalation, ing	gestion (possible, but	

inhalation	Over inhalation of vapor or mist may cause severe irritation to the nose, throat and respiratory tract.
Eye Contact	Irritant to eyes. It may cause tearing, redness and swelling of the eyes.
Skin contact	2-Butoxyethanol penetrates skin readily. Frequent or wide spread contact may result on skin absorption of potentially harmful amounts. Morpholine can cause redness, burning and swelling of the skin.

This is an aerosol product, ingestion is unlikely to occur.

Chemical name	Oral LD50	dermal LD50	Inhalation LC50	
2-Butoxyethanol 111-76-2	= 470 mg/kg(Rat)	= 220 mg/kg (Rabbit)	= 450 ppm (Rat)4 h	
N-Butane 106-97-8	-	-	= 658 g/m <sup>3</sup> (Rat) 4 h	
Morpholine 110-91-8	= 1050 mg/kg(Rat)	= 310 mg/kg (Rabbit)	= 8000 ppm (Rat)8 h	
Propane	-	-	= 658 mg/L (Rat) 4 h	

# 74-98-6

INGESTION

#### Information on toxicological effects

Symptoms Deliberate inhalation of concentrated vapor or mist may cause headache, dizziness and nausea.

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	May cause skin irritation after contact with skin. 2-Butoxyethanol penetrates skin readily. Frequent or wide spread contact may results on skin absorption of potentially harmful amounts.
Serious eye damage/eye irritation	Can cause irritation after contact with the eyes.
corrosivity	Not applicable.
sensitization	No a skin sensitizer.
Germ Cell Mutagenicity	No information available.
carcinogenicity	The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
2-Butoxyethanol 111-76-2	A3	Group 3		
Morpholine 110-91-8		Group 3		

Reproductive Toxicity	No information available.
STOT - single exposure	No information available.
STOT - repeated exposure	No information available.
Aspiration Hazard	Deliberate inhalation of concentrated vapor or mist may cause headache, dizziness and
-	nausea.

Numerical measures of toxicity - Product Information

2.17% of the mixture consists of ingredient(s) of unknown toxicity Unknown acute toxicity The following values are calculated based on chapter 3.1 of the GHS document ATEmix (oral) 4541 mg/kg ATEmix (dermal) 9649 mg/kg ATEmix (inhalation-gas) 7359 mg/l ATEmix (inhalation-dust/mist) 13.2 mg/l ATEmix (inhalation-vapor) 3455 mg/l

#### **12. Ecological Information**

This product does not contain marine pollutants.

#### ecotoxicity

#### 7.17% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical name	Algae/aquatic plants	Fish	Toxicity to Microorganisms	Crustacea
2-Butoxyethanol 111-76-2		1490: 96 h Lepomis macrochirus mg/L LC50 static 2950: 96 h Lepomis macrochirus mg/L LC50		1698 - 1940: 24 h Daphnia magna mg/L EC50 1000: 48 h Daphnia magna mg/L EC50
Morpholine 110-91-8	28: 96 h Pseudokirchneriella subcapitata mg/L EC50 static	350: 96 h Lepomis macrochirus mg/L LC50 static 375 - 460: 96 h Oncorhynchus mykiss mg/L LC50 1000: 96 h Brachydanio rerio mg/L LC50 static	EC50 = 57.0 mg/L 30 min	100: 24 h Daphnia magna mg/L EC50

#### Persistence and degradability

No information available.

#### **Bioaccumulation**

No information available.

Chemical name	Partition coefficient
2-Butoxyethanol 111-76-2	0.81
N-Butane 106-97-8	2.89
Morpholine 110-91-8	-2.55
Propane 74-98-6	2.3

#### Other adverse effects Ozone

No information available

This product does not contain CFCs or other ozone depleting substances. Federal regulations prohibit the use CFC propellants in aerosols.

# **13. Disposal Considerations**

Waste treatment methods	
Disposal of wastes	Dispose of in accordance with federal, state and local regulations.
Contaminated packaging	Pressurized container: Do not pierce or burn, even after use. Do not puncture or incinerate container. If empty: Place in trash or offer for recycling if available. If partly filled: Call your local solid waste agency for disposal instructions.

## 14. Transport Information

DOT	Limited quantity (LQ) Baseboard and wax stripper.
UN/ID no	UN1950
Proper Shipping Name	Limited quantity (LQ)
Hazard Class	2.1
Marine pollutant	This product does not contain marine pollutants.

#### 15. Regulatory information

#### International Inventories TSCA

All ingredients of this product are listed or are excluded from listing under the U.S. Toxic Subtances Control Act (TSCA) Chemical Substance Inventory. All ingredients are listed or are excluded from listing on the DSL.

# DSL

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

#### US Federal Regulations

#### <u>SARA 313</u>

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 and 40 CFR 372. This information must be included in all SDSs that are copied and distributed for this material.

Chemical name	CAS No	weight-%	SARA 313 - Threshold Values %
2-Butoxyethanol - 111-76-2	111-76-2	5-10	1.0

#### SARA 311/312 Hazard Categories

Acute Health Hazard	yes
Chronic Health Hazard	No
Fire Hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

#### CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

#### **CERCLA**

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

#### US State Regulations

#### California Proposition 65

This product does not contain any Proposition 65 chemicals

#### U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
2-Butoxyethanol 111-76-2	Х	X	Х
N-Butane 106-97-8	Х	Х	Х
Morpholine 110-91-8	Х	X	Х
Propane 74-98-6	Х	X	Х

#### U.S. EPA Label information

EPA Pesticide registration number Not applicable

16. Other information				
NFPA	Health Hazards 1	Flammability 1	Instability 1	Physical and chemical properties Not applicable
<u>HMIS</u>	Health Hazards 1	Flammability 2	Physical Hazards 1	Personal Protection B - Eyes and hands protection
at the date of its public	ed in this Material Safe ation. The information	ety Data Sheet is correct given is designed only	t to the best of our knowle as a guidance for safe har ered a warranty or guality	• •

storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet